

Arquivo meetme.conf

```
;
; Configuration file for MeetMe simple conference rooms for Asterisk of course.
;
; This configuration file is read every time you call app meetme()

[general]
;audiobuffers=32; The number of 20ms audio buffers to be used
; when feeding audio frames from non-DAHDI channels
; into the conference; larger numbers will allow
; for the conference to 'de-jitter' audio that arrives
; at different timing than the conference timing
; source, but can also allow for latency in hearing
; the audio from the speaker. Minimum value is 2,
; maximum value is 32.
;
; Conferences may be scheduled from realtime?
;schedule=yes
;
; Update realtime when members login/out of the conference
;logmembercount=no
;
; How much earlier than the start time should we allow participants to
; join the conference (in seconds)?
;fuzzystart=300
;
; If the participants join too early, how much time should we allow
; to tell them that they have joined too early, rather than telling them
; the conference simply doesnt exist (in seconds)?
;earlyalert=3600
;
; How many seconds before the scheduled end of the conference should
; the participants be warned?
;endalert=120
;
[rooms]
;
; Usage is conf => confno[,pin][,adminpin]
;
; Note that once a participant has called the conference, a change to the pin
; number done in this file will not take effect until there are no more users
; in the conference and it goes away. When it is created again, it will have
; the new pin number.
;
conf => 100
```