

1 Arquivo voicemail.conf

```
;!
;! Automatically generated configuration file
;! Filename: voicemail.conf (/etc/asterisk/voicemail.conf)
;! Generator: AppVoicemail
;! Creation Date: Wed May 13 01:47:49 2009
;!
;
; Voicemail Configuration
;
[general]
; Formats for writing Voicemail. Note that when using IMAP storage for
; voicemail, only the first format specified will be used.
;format=g723sf|wav49|wav
format = wav49|gsm|wav
; Who the e-mail notification should appear to come from
serveremail = asterisk
; Should the email contain the voicemail as an attachment
attach = yes
; How many milliseconds to skip forward/back when rew/ff in message playback
skipms = 3000
; How many seconds of silence before we end the recording
maxsilence = 10
; Silence threshold (what we consider silence: the lower, the more sensitive)
silencethreshold = 128
; Max number of failed login attempts
maxlogins = 3

[zonemessages]
eastern = America/New_York|'vm-received' Q 'digits/at' IMp
central = America/Chicago|'vm-received' Q 'digits/at' IMp
central24 = America/Chicago|'vm-received' q 'digits/at' H N 'hours'
military = Zulu|'vm-received' q 'digits/at' H N 'hours' 'phonetic/z_p'
european = Europe/Copenhagen|'vm-received' a d b 'digits/at' HM

[default]
5000 => 1234,Rafa Veiga,rafael@edu.xunta.es
5001 => 1234,Manuel Vieites,vieites@edu.xunta.es
7000 => 1234,informatica,informatica_sc@terra.es
```