

1 Arquivo musiconhold.conf

```
;
; Music on Hold -- Sample Configuration
;
[general]
;cachertclasses=yes ; use 1 instance of moh class for all users who are using it,
;                               ; decrease consumable cpu cycles and memory
;                               ; disabled by default

; valid mode options:
; files      -- read files from a directory in any Asterisk supported
;                               media format
; quietmp3   -- default
; mp3        -- loud
; mp3nb      -- unbuffered
; quietmp3nb -- quiet unbuffered
; custom     -- run a custom application (See examples below)

; =====
; File-based (native) music on hold
; =====
;
; This plays files directly from the specified directory, no external
; processes are required. Files are played in normal sorting order
; (same as a sorted directory listing), and no volume or other
; sound adjustments are available. If the file is available in
; the same format as the channel's codec, then it will be played
; without transcoding (same as Playback would do in the dialplan).
; Files can be present in as many formats as you wish, and the
; 'best' format will be chosen at playback time.
;
; NOTE:
; If you are not using "autoload" in modules.conf, then you
; must ensure that the format modules for any formats you wish
; to use are loaded _before_ res_musiconhold. If you do not do
; this, res_musiconhold will skip the files it is not able to
; understand when it loads.
;

[default]
mode=files
directory=/var/lib/asterisk/moh

[blues]
mode=files
directory=/var/lib/asterisk/moh/blues

[americanas]
mode=files
directory=/var/lib/asterisk/moh/americanas

[pop]
mode=files
directory=/var/lib/asterisk/moh/pop

;
;[native-random]
;mode=files
;directory=/var/lib/asterisk/moh
;digit=#      ; If this option is set for a class, then when callers are
;              ; listening to music on hold, they can press this digit, and
;              ; they will switch to listening to this music class.
;sort=random   ; Sort the files in random order

;[native-alphabetical]
;mode=files
;directory=/var/lib/asterisk/moh
;sort=alpha    ; Sort the files in alphabetical order.  If this option is
;              ; not specified, the sort order is undefined.
```

```
; =====
; Other (non-native) playback methods
; =====

;[manual]
;mode=custom
; Note that with mode=custom, a directory is not required, such as when reading
; from a stream.
;directory=/var/lib/asterisk/mohmp3
;application=/usr/bin/mpg123 -q -r 8000 -f 8192 -b 2048 --mono -s

;[ulawstream]
;mode=custom
;application=/usr/bin/streamplayer 192.168.100.52 888
;format=ulaw

; mpg123 on Solaris does not always exit properly; madplay may be a better
; choice
;[solaris]
;mode=custom
;directory=/var/lib/asterisk/mohmp3
;application=/site/sw/bin/madplay -Q -o raw:- --mono -R 8000 -a -12
```