

# Teléfonos IP

## Configuración dunha IP estática



1. Pulsar no botón **Setup**.
2. Pulsar o número **9** ou navegar ata o opción **Network**.
3. No apartado **1 WAN Connection Type**, pulsar no botón **Edit** e pulsar o botón **option** ata que apareza a opción **Static IP**. Logo pulsar **OK**.
4. Logo ir ao apartado **Non-DHCP IP Address**. Pulsar en **Edit**, e configurarlle a IP estática do teléfono. Empregar a tecla asterisco (\*) en vez de (.). Por exemplo, a dirección IP 192.168.1.60 será escrita como 192\*168\*1\*60. Logo pulsa en **OK**.
5. Ir ao apartado **9 Non-DHCP Subnet Mask**. Pulsar no botón **Edit**, entón introducir a máscara de subrede do teléfono. Pulsar o botón **OK**.
6. No apartado **10 Non-DHCP Default Route**. Pulsar o botón **Edit**, e introducir a porta de enlace por defecto do teléfono IP. Logo pulsar **OK**.
7. Ir ao apartado **11 Non-DHCP DNS 1**. Pulsar o botón **Edit**, e introducir o servidor DNS1 para o teléfono. Pulsar **OK**.
8. Se fose necesario, ir ao apartado **12 Non-DHCP DNS 2** para configurarlle o servidor DNS2.
9. Logo escoller a opción **Save** para grabar todo o configurado.
10. Por último, acceder ao apartado **12 Reboot** e reiniciar o Teléfono.

Configuración despois de entrar pola páxina web do teléfono:

Info	<b>System</b>	SIP	Provisioning	Regional	Phone	Ext 1	Ext 2	Ext 3	Ext 4	User	<a href="#">User Login</a>	<a href="#">basic</a>	<a href="#">advanced</a>
											<a href="#">Personal Directory</a>	<a href="#">Call History</a>	
<b>System Configuration</b>													
Restricted Access Domains: <input type="text"/>													
Enable Web Server: <input type="button" value="yes"/>													
Web Server Port: <input type="text" value="80"/>													
Enable Web Admin Access: <input type="button" value="yes"/>													
Admin Passwd: <input type="text"/>													
User Password: <input type="text"/>													
<b>Internet Connection Type</b>													
Connection Type: <input type="button" value="Static IP"/>													
<b>Static IP Settings</b>													
Static IP: <input type="text" value="192.168.1.60"/>													
NetMask: <input type="text" value="255.255.255.0"/>													
Gateway: <input type="text" value="192.168.1.102"/>													
<b>PPPoE Settings</b>													
PPPoE Login Name: <input type="text"/>													
PPPoE Login Password: <input type="text"/>													
PPPoE Service Name: <input type="text"/>													
<b>Optional Network Configuration</b>													
HostName: <input type="text"/>													
Domain: <input type="text"/>													
Primary DNS: <input type="text" value="192.168.1.4"/>													
Secondary DNS: <input type="text"/>													
DNS Server Order: <input type="button" value="Manual"/>													
DNS Query Mode: <input type="button" value="Parallel"/>													
Syslog Server: <input type="text"/>													
Debug Server: <input type="text"/>													
Debug Level: <input type="button" value="0"/>													
Primary NTP Server: <input type="text"/>													
Secondary NTP Server: <input type="text"/>													
<b>VLAN Settings</b>													
Enable VLAN: <input type="button" value="no"/>													
VLAN ID: <input type="text" value="1"/>													
Enable CDP: <input type="button" value="yes"/>													
<input type="button" value="Undo All Changes"/> <input type="button" value="Submit All Changes"/>													

Estado da configuración visto dende a páxina web do teléfono:

<div>  <div> <b>LINKSYS®</b>  A Division of Cisco Systems, Inc. </div> <div> <b>Linksys Telephone Configuration</b> </div> </div>													
Info	<b>System</b>	SIP	Provisioning	Regional	Phone	Ext 1	Ext 2	Ext 3	Ext 4	User	<a href="#">User Login</a>	<a href="#">basic</a>	<a href="#">advanced</a>
											<a href="#">Personal Directory</a>	<a href="#">Call History</a>	
<b>System Information</b>													
DHCP: <input type="text" value="Static IP"/>													
Current IP: <input type="text" value="192.168.1.60"/>													
Host Name: <input type="text" value="SipuraSPA"/>													
Domain: <input type="text"/>													
Current Netmask: <input type="text" value="255.255.255.0"/>													
Current Gateway: <input type="text" value="192.168.1.102"/>													
Primary DNS: <input type="text" value="192.168.1.4"/>													
Secondary DNS: <input type="text"/>													
<b>Product Information</b>													
Product Name: <input type="text" value="SPA-942"/>													
Serial Number: <input type="text" value="4LO00HB09177"/>													
Software Version: <input type="text" value="5.1.15(a)"/>													
Hardware Version: <input type="text" value="1.0.3(524f)"/>													
MAC Address: <input type="text" value="000E08D456A7"/>													
Client Certificate: <input type="text" value="Installed"/>													
Customization: <input type="text" value="Open"/>													
Licenses: <input type="text" value="None"/>													